

VIGOR

VACP-40B

軟板開窗機 FPCB DIE CUTTING PRESS

用途：

軟式印刷電路板、液晶片、絕緣片、
薄膜按鍵、冷光片、觸控面板等，
銅、錫、鋁各種高精度裁切。

APPLICATION:

Suitable for flexible printed circuit board, LCD, insulation sheet, film key, cold light sheet, touch-sensing screen etc.

High precision cutting for copper, tin and aluminum etc.



VACP-40B

活全機器股份有限公司
VIGOR MACHINERY CO., LTD.



軟板開窗機 FPCB DIE CUTTING PRESS

VACP-40B

特點：

1. 符合人體工學操作高度，操作性佳。
2. 可採雙邊操作功能，提高產能。
3. 採高效率油壓系統，耗電量小。
4. 具高精度裁切深度微調功能，產品不留鬚邊。
5. 採雙手啓動裝置，確保人身安全。
6. 前後送料單元以精密線性滑軌並搭配浮動功能，減少元件磨耗產生，強化機械可靠度。
7. 機台耐壓板採鑄造成型，精密加工成型，無焊接件加工後變形疑慮。
8. 耐壓板夾模大柱採用自潤軸承無需潤滑，減少二次污染疑慮。
9. 本機採低噪音、高效能、佔地空間小設計，樓上樓下任何位置皆方便。
10. 本機使用全封式護蓋設計，便於無塵室使用。

FEATURES:

1. Proper height design for ergonomical operation with superior operational performance.
2. Allows for double sides operation for greatly increasing productivity.
3. High efficiency hydraulic system features lower electricity consumption.
4. High precision micrometric adjustment for cutting depth permits burr-free cutting.
5. Two hands simultaneous starting design for operator's safety guard.
6. Front and back feed systems move on precision linear motion guides combined with floating function to minimize parts wear while upgrading operational dependability.
7. The pressure-resistant plate is manufactured from cast iron, precision machined without deformation caused by welding.
8. The tie bars for pressure resistant plate employ self-lubrication bearings. No further lubrication is required and no second pollution.
9. Low noise running, high performance, and small space occupied. Suitable for operation at any location upstairs or downstairs.
10. Fully enclosed splash guard makes the machine suitable for operation in clean room.

規格表 SPECIFICATIONS

項目 ITEM	型號 MODEL	VACP-40B
油缸 output Hydraulic cylinder output force		40000 kgs
工作台面積 Table area		610 x 670 mm
刀模可用面積 Applicable area of knife edge die		610 x 650 mm
開模行程 Mold open stroke		80 mm
最大間距 Daylight opening		110 mm
行程 Stroke		1~80 mm
機台消耗功率 Power consumption		4 Kw
外觀尺寸 Machine dimensions		1710(L) x 1200(W) x 1700(H) mm
重量 Weight		3000 kgs

活全機器股份有限公司
VIGOR MACHINERY CO., LTD.
台中縣霧峰鄉五福路798號
NO. 798, Wu-Fu Rd., Wu-Feng Hsiang, Taichung Hsien, Taiwan.
Tel:886-4-2331-3388 Fax:886-4-2331-3377 http://www.supvigor.com.tw
E-mail:c.s.huang@seed.net.tw E-mail:sa-2@supvigor.com.tw

大陸辦事處:
廣東省東莞市長安鎮新安社區新安二路9號
Tel:0769-2399-4598 Fax:0755-8149-0041 服務專線:13825252995
江蘇省蘇州市吳中區碧波街遠洋花園4單元307室
Tel:0512-6267-5616 Fax:0512-6513-8125 服務專線:13862422338